

	MULTI-USE	LOOSEN	LUBRICATE					CLEAN	
★ GOOD									
★★★ BETTER									
★★★★★ BEST									
LOOSEN	★	★★★★							
LUBRICATE SHORT-TERM MOVING PARTS	★	★	★★★★	★★★	★★★★	★★★	★★★★		
LUBRICATE LONG-TERM MOVING PARTS			★	★★	★★	★★★★	★★★★		
REMOVE DIRT								★★	★★★★
REMOVE RUST	★	★★★★							
IN DRY/DUSTY CONDITIONS	★	★	★	★★★★	★★	★	★	★★★★	★★★★
IN HUMID CONDITIONS	★★	★★★★	★	★	★★★★	★★★★	★★★★	★★★★	★★★★
PROTECT AGAINST RUST & CORROSION	★★	★★		★	★★★★	★★★★	★★★★		
HIGH-PRESSURE RESISTANCE	★	★	★★★★	★★★★	★★★★	★★★★	★★★★		
TEMPERATURE RANGE	 -20°C to +90°C	 -20°C to +90°C	 -20°C to +160°C	 -45°C to +90°C	 -35°C to +200°C	 Grease -20°C - +115°C, Liquid up to +260°C	 -35°C to +130°C	 Room Temperature	 Room Temperature
MOST COMPATIBLE WITH	Metal, Plastic, Rubber	Metal, Plastic, Rubber	Metal	Metal, Plastic, Glass, Wood	Plastic & Rubber	Vertical Metal & Plastic Surfaces	Heavy Metal-to-Metal Connections	Electrical Contacts	Metals
NOT COMPATIBLE WITH	Soft Rubber	Soft Rubber			Pre-Paintwork		Untested on Plastic & Rubber		Plastic & Rubber

